

YJOT 亿嘉

科技改变未来

CM300i

One-dimensional red light fixed barcode reader

- Excellent decoding ability
- Humanized light source
- Powerful data editing function
- Reliable and durable structural design



Product characteristics

Excellent decoding ability

Scanning and decoding speed is extremely fast, with 700 scans per second, which can scan the fast moving one-dimensional bar code.

Humanized light source

Red bar LED light source can not only avoid visual fatigue in continuous high-strength working pieces, but also greatly improve the operation efficiency.

Powerful data editing function

Powerful data editing function, can flexibly meet all kinds of data editing requirement.

Reliable and durable structural design

It can withstand repeated drops from 0.6 meters high to the cement floor, making the product has excellent reliability and stability.

CM300i

One-dimensional red light fixed
barcode reader

electrical characteristics	
data interface	RS232
working voltage	DC 5V±5%
working current	220mA
optical characteristics	
sensor	CCD linear sensor
sensor resolution	2048 pixel
performance characteristics	
scan distance	20~55mm@Code128(8mil)
	20~55mm@Code39(8mil)
scanning rate	700fps
reading angle	bias: ±30°; shifting: ±60°; revolve: ±10°
minimum resolution	4mil
minimum print contrast ratio	>45%UPC/EAN 13(13mil)
curvature	R > 20mm (EAN8) , R > 30mm (EAN13)
decoding ability	Codabar/NW-7,Code39, Code93,Code128,GS1-128(EAN-128), Industrial 2of5, Interleaved 2of5,IATA,JAN/UPC/EAN incl. add on,MSI/Plessey
physical characteristics	
size	52 mm X55 mm X20mm (long×wide×high)
weight	100g (excluding cable)
aseismic capacity	0.6M drop down to the concrete surface
environmental characteristics	
temperature	0°C-40°C (work) , -10°C-60°C (store up)
humidity	20%~90%
light resistance	5000lux

dimensional drawing:

